



Catalyst Guard

PRODUCT FEATURES

- Saves Money
- 400 Shots per Can
- Extends Shelf Life
- Keep Catalyst Fresh and in Optimal Condition

866-637-8418 • www.axiscoatings.com

»DESCRIPTION

CATALYST GUARD is designed to prolong the life of urethane 2K hardeners by eliminating the air and humidity in the hardener, allowing it to stay fresh. Just spray it in the hardener every time it's used; it pays for itself in just the first use!

»AVAILABILITY

AAP-0900-3 Catalyst Guard Aerosol

»INSTRUCTIONS

Each time a urethane hardener is used, spray 2 one second bursts of the CATALYST GUARD on to hardener. DO NOT TURN CAN UPSIDE DOWN. DO NOT SHAKE. Just spray and go. Close hardener after spraying with CATALYST GUARD.

»TECHNICAL DATA

Color:	n/a
Flash Point	-156°F
Recommended Film Build	n/a
Pot Life	n/a
Mix Ratio	Ready to use
Sprayable Viscosity (RTS)	n/a
Weight Solids (RTS)	0%
VOC Content (RTS)	4.35 lb/gal



»DISTRIBUTED BY«

WARRANTY:

All recommendations for the use of AXIS Performance Coating Products are based on tests and experience believed to be reliable. Since the methods of use, conditions of application and the application itself are beyond our control, product warranty can be restricted to replacement of materials only.