

SAFETY DATA SHEET

Revision Date 19-May-2015

Version 1

1. IDENTIFICATION

Product identifier

Product Name Victory Acrylic Urethane Clear

Other means of identification

Product Code ACL-1100-4
UN/ID no. UN1263
SKU(s) ACL-1100-1, ACL-1100-4

Recommended use of the chemical and restrictions on use

Recommended Use No information available.
Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Address

Vogel Automotive Coatings
1020 Albany Place SE
Orange City, IA 51041
Phone: 712-737-4993
Fax: 712-737-4997

Emergency telephone number

Emergency Telephone Chemtrec 1-800-424-9300

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Emergency Overview

Danger

Hazard statements

Causes serious eye irritation
May cause genetic defects
May cause cancer
May cause drowsiness or dizziness
May be fatal if swallowed and enters airways
Highly flammable liquid and vapor



Appearance No information available

Physical state liquid

Odor No information available

Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Avoid breathing dust/fume/gas/mist/vapors/spray
- Use only outdoors or in a well-ventilated area
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Keep container tightly closed
- Ground/bond container and receiving equipment
- Use only non-sparking tools
- Take precautionary measures against static discharge
- Keep cool
- Use explosion-proof electrical/ ventilating/ lighting/ equipment

Precautionary Statements - Response

- IF exposed or concerned: Get medical advice/attention
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- If eye irritation persists: Get medical advice/attention
- IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
- IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
- Do NOT induce vomiting
- In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

- Store locked up
- Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

- Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- Toxic to aquatic life with long lasting effects
- Unknown acute toxicity 2.06% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Butyl Acetate	123-86-4	10 - 30	*
Aromatic 150	64742-94-5	5 - 10	*
Acetone	67-64-1	5 - 10	*
Tert-Butyl Acetate	540-88-5	5 - 10	*
Aromatic 100	64742-95-6	3 - 7	*
Methyl Ethyl Ketone	78-93-3	1 - 5	*
1,2,4-Trimethylbenzene	95-63-6	1 - 5	*
Methyl Amyl Ketone	110-43-0	1 - 5	*

Parachlorobenzotrifluoride	98-56-6	1 - 5	*
Xylene	1330-20-7	1 - 5	*
Naphthalene	91-20-3	0.1 - 1	*
Ethyl Benzene	100-41-4	0.1 - 1	*
Cumene	98-82-8	0.1 - 1	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

- General advice** Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
- Eye contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
- Skin Contact** Wash off immediately with plenty of water. Call a physician immediately.
- Inhalation** Remove to fresh air. Call a physician. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Move victim to fresh air. If not breathing, give artificial respiration. Call a physician immediately.
- Ingestion** Do NOT induce vomiting. Rinse mouth. Drink plenty of water. If symptoms persist, call a physician. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.
- Self-protection of the first aider** Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Extremely flammable.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

Incompatible materials Strong acids. Strong oxidizing agents. Chlorinated compounds.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Butyl Acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³
Tert-Butyl Acetate 540-88-5	TWA: 200 ppm	TWA: 200 ppm TWA: 950 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 950 mg/m ³	IDLH: 1500 ppm TWA: 200 ppm TWA: 950 mg/m ³

Methyl Ethyl Ketone 78-93-3	STEL: 300 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 590 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 590 mg/m ³ (vacated) STEL: 300 ppm (vacated) STEL: 885 mg/m ³	IDLH: 3000 ppm TWA: 200 ppm TWA: 590 mg/m ³ STEL: 300 ppm STEL: 885 mg/m ³
1,2,4-Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
Methyl Amyl Ketone 110-43-0	TWA: 50 ppm	TWA: 100 ppm TWA: 465 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 465 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 465 mg/m ³
Parachlorobenzotrifluoride 98-56-6	TWA: 2.5 mg/m ³ F	TWA: 2.5 mg/m ³ F TWA: 2.5 mg/m ³ dust (vacated) TWA: 2.5 mg/m ³	-
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection

Tight sealing safety goggles.

Skin and body protection

No special technical protective measures are necessary.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid	Odor	No information available
Appearance	No information available	Odor threshold	No information available
Color	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point/freezing point	No information available	
Boiling point / boiling range	>= 110 °C / 133 °F	
Flash point	9 °C / 1 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	0.95	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	8.98 lbs/gal
Bulk density	No information available
Percent solids by weight	37.2%
Percent volatile by weight	45.2%
Percent solids by volume	31.1%
Actual VOC (lbs/gal)	3.6
Actual VOC (grams/liter)	428.5
EPA VOC (lbs/gal)	4.4
EPA VOC (grams/liter)	530.8
EPA VOC (lb/gal solids)	11.5

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Chlorinated compounds.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	No data available
Inhalation	No data available.
Eye contact	No data available.
Skin Contact	No data available.
Ingestion	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Butyl Acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Aromatic 150 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h
Acetone 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h
Tert-Butyl Acetate 540-88-5	= 4100 mg/kg (Rat)	> 2 g/kg (Rabbit)	> 2230 mg/m ³ (Rat) 4 h
Aromatic 100 64742-95-6	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
Methyl Ethyl Ketone 78-93-3	= 2483 mg/kg (Rat) = 2737 mg/kg (Rat)	= 5000 mg/kg (Rabbit) = 6480 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Methyl Amyl Ketone 110-43-0	= 1600 mg/kg (Rat) = 1670 mg/kg (Rat)	= 12.6 mL/kg (Rabbit) = 12600 µL/kg (Rabbit)	> 2000 ppm (Rat) 4 h
Parachlorobenzotrifluoride 98-56-6	= 13 g/kg (Rat)	> 2 mL/kg (Rabbit)	= 33 mg/L (Rat) 4 h
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Naphthalene 91-20-3	= 1110 mg/kg (Rat) = 490 mg/kg (Rat)	(= 1120 mg/kg (Rabbit) > 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h
Ethyl Benzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	= 39000 mg/m ³ (Rat) 4 h > 3577 ppm (Rat) 6 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X
Ethyl Benzene 100-41-4	A3	Group 2B	-	X
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)
 Group 2B - Possibly Carcinogenic to Humans
 Group 3 - Not classifiable as a human carcinogen
 NTP (National Toxicology Program)
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present

Reproductive toxicity No information available.
STOT - single exposure No information available.
STOT - repeated exposure No information available.
Chronic toxicity Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. May cause adverse effects on the bone marrow and blood-forming system.
Target Organ Effects blood, Central nervous system, Eyes, Peripheral Nervous System (PNS), Respiratory system, Skin.
Aspiration hazard No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

2.1% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Butyl Acetate 123-86-4	674.7: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	100: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 17 - 19: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 62: 96 h <i>Leuciscus idus</i> mg/L LC50 static	72.8: 24 h <i>Daphnia magna</i> mg/L EC50
Aromatic 150 64742-94-5	2.5: 72 h <i>Skeletonema costatum</i> mg/L EC50	19: 96 h <i>Pimephales promelas</i> mg/L LC50 static 2.34: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 1740: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 45: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 41: 96 h <i>Pimephales promelas</i> mg/L LC50	0.95: 48 h <i>Daphnia magna</i> mg/L EC50
Acetone 67-64-1	-	4.74 - 6.33: 96 h <i>Oncorhynchus mykiss</i> mL/L LC50 6210 - 8120: 96 h <i>Pimephales promelas</i> mg/L LC50 static 8300: 96 h <i>Lepomis macrochirus</i> mg/L LC50	10294 - 17704: 48 h <i>Daphnia magna</i> mg/L EC50 Static 12600 - 12700: 48 h <i>Daphnia magna</i> mg/L EC50
Tert-Butyl Acetate 540-88-5	-	296 - 362: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through	-
Aromatic 100 64742-95-6	-	9.22: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50	6.14: 48 h <i>Daphnia magna</i> mg/L EC50
Methyl Ethyl Ketone 78-93-3	-	3130 - 3320: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through	520: 48 h <i>Daphnia magna</i> mg/L EC50 5091: 48 h <i>Daphnia magna</i> mg/L EC50 4025 - 6440: 48 h <i>Daphnia magna</i> mg/L EC50 Static
1,2,4-Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through	6.14: 48 h <i>Daphnia magna</i> mg/L EC50
Methyl Amyl Ketone 110-43-0	-	126 - 137: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through	-
Parachlorobenzotrifluoride 98-56-6	-	11.5 - 15.8: 48 h <i>Lepomis macrochirus</i> mg/L LC50 static	3.68: 48 h <i>Daphnia magna</i> mg/L EC50

Xylene 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Naphthalene 91-20-3	0.4: 72 h Skeletonema costatum mg/L EC50	5.74 - 6.44: 96 h Pimephales promelas mg/L LC50 flow-through 1.6: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 0.91 - 2.82: 96 h Oncorhynchus mykiss mg/L LC50 static 1.99: 96 h Pimephales promelas mg/L LC50 static 31.0265: 96 h Lepomis macrochirus mg/L LC50 static	2.16: 48 h Daphnia magna mg/L LC50 1.96: 48 h Daphnia magna mg/L EC50 Flow through 1.09 - 3.4: 48 h Daphnia magna mg/L EC50 Static
Ethyl Benzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Cumene 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Butyl Acetate 123-86-4	1.81
Aromatic 150 64742-94-5	2.9 - 6.1
Acetone 67-64-1	-0.24
Tert-Butyl Acetate 540-88-5	1.38
Methyl Ethyl Ketone 78-93-3	0.29
1,2,4-Trimethylbenzene 95-63-6	3.63
Methyl Amyl Ketone 110-43-0	1.98
Parachlorobenzotrifluoride 98-56-6	3.7
Xylene 1330-20-7	2.77 - 3.15

Naphthalene 91-20-3	3.3
Ethyl Benzene 100-41-4	3.118
Cumene 98-82-8	3.55

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U002 U055 U159 U165 U220 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Acetone 67-64-1	-	Included in waste stream: F039	-	U002
Methyl Ethyl Ketone 78-93-3	U159	Included in waste streams: F005, F039	200.0 mg/L regulatory level	U159
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145	-	U165
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-
Cumene 98-82-8	-	-	-	U055

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Butyl Acetate 123-86-4	Toxic
Acetone 67-64-1	Ignitable
Methyl Ethyl Ketone 78-93-3	Toxic Ignitable

Xylene 1330-20-7	Toxic Ignitable
Naphthalene 91-20-3	Toxic
Ethyl Benzene 100-41-4	Toxic Ignitable
Cumene 98-82-8	Toxic Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class Class 3, Flammable Liquid

Packing Group II
 Special Provisions 149, B52, IB2, T4, TP1, TP8, TP28
 Emergency Response Guide Number 128

TDG

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II

MEX

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II

ICAO (air)

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II
 Special Provisions A3, A72

IATA

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II
 ERG Code 3L
 Special Provisions A3, A72

IMDG

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3
 Packing Group II
 EmS-No. F-E, S-E
 Special Provisions 163
 Description UN1263, Paint, 3, II

RID

UN/ID no. UN1263
 Proper shipping name Paint
 Hazard Class 3

Packing Group II
Classification code F1

ADR

UN/ID no. UN1263
Proper shipping name Paint
Hazard Class 3
Packing Group II
Classification code F1
Tunnel restriction code (D/E)
Special Provisions 163, 640C, 650
Labels 3

ADN

Proper shipping name Paint
Hazard Class 3
Packing Group II
Classification code F1
Special Provisions 163, 640C, 650
Hazard label(s) 3
Limited quantity (LQ) 5 L
Ventilation VE01

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies *
EINECS/ELINCS Does not comply *
ENCS Does not comply *
IECSC Complies *
KECL Complies *
PICCS Complies *
AICS Complies *

* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
1,2,4-Trimethylbenzene - 95-63-6	1.0
Xylene - 1330-20-7	1.0
Naphthalene - 91-20-3	0.1
Ethyl Benzene - 100-41-4	0.1

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No

Reactive Hazard

No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl Acetate 123-86-4	5000 lb	-	-	X
Tert-Butyl Acetate 540-88-5	-	-	-	X
Xylene 1330-20-7	100 lb	-	-	X
Naphthalene 91-20-3	100 lb	X	X	X
Ethyl Benzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Butyl Acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Tert-Butyl Acetate 540-88-5	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Methyl Ethyl Ketone 78-93-3	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Naphthalene 91-20-3	100 lb 1 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Naphthalene - 91-20-3	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen
Toluene - 108-88-3	Developmental Female Reproductive

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Butyl Acetate 123-86-4	X	X	X
Acetone 67-64-1	X	X	X
Tert-Butyl Acetate 540-88-5	X	X	X
Methyl Ethyl Ketone 78-93-3	X	X	X
1,2,4-Trimethylbenzene 95-63-6	X	X	X

Methyl Amyl Ketone 110-43-0	X	X	X
Parachlorobenzotrifluoride 98-56-6	X	-	X
Xylene 1330-20-7	X	X	X
Naphthalene 91-20-3	X	X	X
Ethyl Benzene 100-41-4	X	X	X
Cumene 98-82-8	X	X	X
Solvent Naphtha, Medium Aliphatic 64742-88-7	X	-	-
Toluene 108-88-3	X	X	X
Diethylene Glycol Methyl Ether 111-77-3	X	X	X
2-Ethylhexanoic acid 149-57-5	X	-	-

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

Hazardous air pollutants (HAPS) content

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

Chemical Name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Xylene 1330-20-7	1.96%	0.15

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 Physical and Chemical Properties -
HMIS Health hazards 2 * Flammability 3 Physical hazards 0 Personal protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Revision Date 19-May-2015

Revision Note
No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

End of Safety Data Sheet