

# SAFETY DATA SHEET

Revision Date 18-May-2015

Version 2

## 1. IDENTIFICATION

### Product identifier

**Product Name** Versaprime 2K HB - Buff

### Other means of identification

**Product Code** APR-1263-4  
**UN/ID no.** UN1263  
**SKU(s)** APR-1263-1, APR-1263-4

### Recommended use of the chemical and restrictions on use

**Recommended Use** No information available.  
**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### **Supplier Address**

Vogel Automotive Coatings  
1020 Albany Place SE  
Orange City, IA 51041  
Phone: 712-737-4993  
Fax: 712-737-4997

### Emergency telephone number

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2
Flammable liquids	Category 2

### Emergency Overview

#### **Danger**

#### **Hazard statements**

Causes skin irritation  
May cause genetic defects  
May cause cancer  
Suspected of damaging fertility or the unborn child  
May cause damage to organs through prolonged or repeated exposure  
Highly flammable liquid and vapor

**Appearance** No information available**Physical state** liquid**Odor** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other Information**

Unknown acute toxicity 44.77% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Calcium carbonate	1317-65-3	15 - 40	*
Butyl Acetate	123-86-4	7 - 13	*
Titanium dioxide	13463-67-7	5 - 10	*
Xylene	1330-20-7	5 - 10	*
Talc (powder)	14807-96-6	5 - 10	*
Ethyl Benzene	100-41-4	1 - 5	*
Toluene	108-88-3	1 - 5	*
Aromatic 100	64742-95-6	1 - 5	*
Crystalline Silica	14808-60-7	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**Description of first aid measures**

<b>General advice</b>	Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
<b>Eye contact</b>	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin Contact</b>	Wash off immediately with plenty of water. Call a physician immediately.
<b>Inhalation</b>	Move victim to fresh air. If not breathing, give artificial respiration. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.
<b>Self-protection of the first aider</b>	Remove all sources of ignition.

**Most important symptoms and effects, both acute and delayed**

<b>Symptoms</b>	No information available.
-----------------	---------------------------

**Indication of any immediate medical attention and special treatment needed**

<b>Note to physicians</b>	Treat symptomatically.
---------------------------	------------------------

**5. FIRE-FIGHTING MEASURES****Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

**Specific hazards arising from the chemical**

Flammable.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required.
-----------------------------	---

**Environmental precautions**

<b>Environmental precautions</b>	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.
----------------------------------	---

**Methods and material for containment and cleaning up**

<b>Methods for containment</b>	Prevent further leakage or spillage if safe to do so.
--------------------------------	---

**Methods for cleaning up** Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

**Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product.

### Conditions for safe storage, including any incompatibilities

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong oxidizing agents. Strong acids. Chlorinated compounds.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Calcium carbonate 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust
Butyl Acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
Titanium dioxide 13463-67-7	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	IDLH: 5000 mg/m <sup>3</sup>
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Talc (powder) 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>

Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
Crystalline Silica 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable fraction	(vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (30)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA total dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust TWA: 0.05 mg/m <sup>3</sup> respirable dust

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information** Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection** No special technical protective measures are necessary.

**Skin and body protection** No special technical protective measures are necessary.

**Respiratory protection** If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**General Hygiene Considerations** When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	No information available
<b>Appearance</b>	No information available	<b>Odor threshold</b>	No information available
<b>Color</b>	No information available		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point/freezing point	No information available	
Boiling point / boiling range	>= 110 °C / 230 °F	
Flash point	18 °C / 64 °F	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	1.51	
Water solubility	No information available	
Solubility in other solvents	No information available	

<b>Partition coefficient</b>	No information available
<b>Autoignition temperature</b>	No information available
<b>Decomposition temperature</b>	No information available
<b>Kinematic viscosity</b>	No information available
<b>Dynamic viscosity</b>	No information available
<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Density</b>	12.60 lbs/gal
<b>Bulk density</b>	No information available
<b>Percent solids by weight</b>	71.1%
<b>Percent volatile by weight</b>	28.9%
<b>Percent solids by volume</b>	51.5%
<b>Actual VOC (lbs/gal)</b>	3.6
<b>Actual VOC (grams/liter)</b>	437
<b>EPA VOC (lbs/gal)</b>	3.6
<b>EPA VOC (grams/liter)</b>	437
<b>EPA VOC (lb/gal solids)</b>	7.1

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents. Strong acids. Chlorinated compounds.

**Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Product Information</b>	No data available
<b>Inhalation</b>	No data available.
<b>Eye contact</b>	No data available.
<b>Skin Contact</b>	No data available.
<b>Ingestion</b>	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Butyl Acetate 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h

Titanium dioxide 13463-67-7	> 10000 mg/kg ( Rat )	-	-
Xylene 1330-20-7	= 3500 mg/kg ( Rat )	> 1700 mg/kg ( Rabbit ) > 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Ethyl Benzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
Toluene 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
Aromatic 100 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
Crystalline Silica 14808-60-7	= 500 mg/kg ( Rat )	-	-

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Xylene 1330-20-7	-	Group 3	-	-
Talc (powder) 14807-96-6	-	Group 3	-	-
Ethyl Benzene 100-41-4	A3	Group 2B	-	X
Toluene 108-88-3	-	Group 3	-	-
Crystalline Silica 14808-60-7	A2	Group 1	Known	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive toxicity** Product is or contains a chemical which is a known or suspected reproductive hazard.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic toxicity**

Contains a known or suspected reproductive toxin. Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. May cause adverse liver effects.

**Target Organ Effects**

Central nervous system, Central Vascular System (CVS), Eyes, kidney, liver, lungs, Respiratory system, Skin.

**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

**12. ECOLOGICAL INFORMATION****Ecotoxicity**

46.41% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Butyl Acetate 123-86-4	674.7: 72 h <i>Desmodesmus subspicatus</i> mg/L EC50	100: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 17 - 19: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 62: 96 h <i>Leuciscus idus</i> mg/L LC50 static	72.8: 24 h <i>Daphnia magna</i> mg/L EC50
Xylene 1330-20-7	-	13.4: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 2.661 - 4.093: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 13.5 - 17.3: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 13.1 - 16.5: 96 h <i>Lepomis macrochirus</i> mg/L LC50 flow-through 19: 96 h <i>Lepomis macrochirus</i> mg/L LC50 7.711 - 9.591: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 23.53 - 29.97: 96 h <i>Pimephales promelas</i> mg/L LC50 static 780: 96 h <i>Cyprinus carpio</i> mg/L LC50 semi-static 780: 96 h <i>Cyprinus carpio</i> mg/L LC50 30.26 - 40.75: 96 h <i>Poecilia reticulata</i> mg/L LC50 static	3.82: 48 h water flea mg/L EC50 0.6: 48 h <i>Gammarus lacustris</i> mg/L LC50
Talc (powder) 14807-96-6	-	100: 96 h <i>Brachydanio rerio</i> g/L LC50 semi-static	-
Ethyl Benzene 100-41-4	4.6: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 438: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 2.6 - 11.3: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static 1.7 - 7.6: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static	11.0 - 18.0: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 4.2: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 semi-static 7.55 - 11: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 32: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 9.1 - 15.6: 96 h <i>Pimephales promelas</i> mg/L LC50 static 9.6: 96 h <i>Poecilia reticulata</i> mg/L LC50 static	1.8 - 2.4: 48 h <i>Daphnia magna</i> mg/L EC50
Toluene 108-88-3	433: 96 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 12.5: 72 h <i>Pseudokirchneriella subcapitata</i> mg/L EC50 static	15.22 - 19.05: 96 h <i>Pimephales promelas</i> mg/L LC50 flow-through 12.6: 96 h <i>Pimephales promelas</i> mg/L LC50 static 5.89 - 7.81: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 flow-through 14.1 - 17.16: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 static 5.8: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50 semi-static 11.0 - 15.0: 96 h <i>Lepomis macrochirus</i> mg/L LC50 static 54: 96 h <i>Oryzias latipes</i> mg/L LC50 static 28.2: 96 h <i>Poecilia reticulata</i> mg/L LC50 semi-static 50.87 - 70.34: 96 h <i>Poecilia reticulata</i> mg/L LC50 static	5.46 - 9.83: 48 h <i>Daphnia magna</i> mg/L EC50 Static 11.5: 48 h <i>Daphnia magna</i> mg/L EC50
Aromatic 100 64742-95-6	-	9.22: 96 h <i>Oncorhynchus mykiss</i> mg/L LC50	6.14: 48 h <i>Daphnia magna</i> mg/L EC50

**Persistence and degradability**

No information available.

**Bioaccumulation**

No information available.

Chemical Name	Partition coefficient
Butyl Acetate 123-86-4	1.81
Xylene 1330-20-7	2.77 - 3.15
Ethyl Benzene 100-41-4	3.118



Toluene 108-88-3	2.65
---------------------	------

**Other adverse effects** No information available

### 13. DISPOSAL CONSIDERATIONS

#### Waste treatment methods

**Disposal of wastes** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001 U055 U220 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	U220

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Butyl Acetate 123-86-4	Toxic
Xylene 1330-20-7	Toxic Ignitable
Ethyl Benzene 100-41-4	Toxic Ignitable
Toluene 108-88-3	Toxic Ignitable

### 14. TRANSPORT INFORMATION

#### DOT

**UN/ID no.** UN1263  
**Proper shipping name** Paint

<b>Hazard Class</b>	Class 3, Flammable Liquid
<b>Packing Group</b>	II
<b>Special Provisions</b>	149, B52, IB2, T4, TP1, TP8, TP28
<b>Description</b>	UN1263, Paint, Class 3, Flammable Liquid, II
<b>Emergency Response Guide Number</b>	128

**TDG**

<b>UN/ID no.</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1263, Paint, 3, II

**MEX**

<b>UN/ID no.</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Description</b>	UN1263, Paint, 3, II

**ICAO (air)**

<b>UN/ID no.</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Special Provisions</b>	A3, A72
<b>Description</b>	UN1263, Paint, 3, II

**IATA**

<b>UN/ID no.</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>ERG Code</b>	3L
<b>Special Provisions</b>	A3, A72
<b>Description</b>	UN1263, Paint, 3, II

**IMDG**

<b>UN/ID no.</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>EmS-No.</b>	F-E, S-E
<b>Special Provisions</b>	163
<b>Description</b>	UN1263, Paint, 3, II

**RID**

<b>UN/ID no.</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Classification code</b>	F1
<b>Description</b>	UN1263, Paint, 3, II

**ADR**

<b>UN/ID no.</b>	UN1263
<b>Proper shipping name</b>	Paint
<b>Hazard Class</b>	3
<b>Packing Group</b>	II
<b>Classification code</b>	F1

Tunnel restriction code (D/E)  
 Special Provisions 163, 640C, 650  
 Description UN1263, Paint, 3, II, (D/E)  
 Labels 3

**ADN**

Proper shipping name Paint  
 Hazard Class 3  
 Packing Group II  
 Classification code F1  
 Special Provisions 163, 640C, 650  
 Description UN1263, Paint, 3, II  
 Hazard label(s) 3  
 Limited quantity (LQ) 5 L  
 Ventilation VE01

**15. REGULATORY INFORMATION****International Inventories**

TSCA Complies  
 DSL/NDSL Complies \*  
 EINECS/ELINCS Complies \*  
 ENCS Does not comply \*  
 IECSC Complies \*  
 KECL Complies \*  
 PICCS Complies \*  
 AICS Complies \*

\* This product contains an unknown chemical, therefore, this product's compliance to the inventory list is NOT DETERMINED

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory  
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List  
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
 ENCS - Japan Existing and New Chemical Substances  
 IECSC - China Inventory of Existing Chemical Substances  
 KECL - Korean Existing and Evaluated Chemical Substances  
 PICCS - Philippines Inventory of Chemicals and Chemical Substances  
 AICS - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Xylene - 1330-20-7	1.0
Ethyl Benzene - 100-41-4	0.1
Toluene - 108-88-3	1.0

**SARA 311/312 Hazard Categories**

Acute health hazard Yes  
 Chronic Health Hazard Yes  
 Fire hazard Yes  
 Sudden release of pressure hazard No  
 Reactive Hazard No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances

Butyl Acetate 123-86-4	5000 lb	-	-	X
Xylene 1330-20-7	100 lb	-	-	X
Ethyl Benzene 100-41-4	1000 lb	X	X	X
Toluene 108-88-3	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Butyl Acetate 123-86-4	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Toluene 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethyl Benzene - 100-41-4	Carcinogen
Toluene - 108-88-3	Developmental Female Reproductive
Crystalline Silica - 14808-60-7	Carcinogen
Cumene - 98-82-8	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Calcium carbonate 1317-65-3	X	X	X
Butyl Acetate 123-86-4	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Xylene 1330-20-7	X	X	X
Talc (powder) 14807-96-6	X	X	X
Ethyl Benzene 100-41-4	X	X	X
Toluene 108-88-3	X	X	X
Crystalline Silica 14808-60-7	X	X	X
Ethylene Glycol Butyl Ether 111-76-2	X	X	X
Cumene 98-82-8	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**Hazardous air pollutants (HAPS) content**

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants':

