

# SAFETY DATA SHEET

Revision Date 03-Feb-2017

Version 5

## 1. IDENTIFICATION

### Product identifier

**Product Name** Mirror Clear II Activator (Panel)

### Other means of identification

**Product Code** BCL-1217-4  
**UN/ID no.** UN1263  
**SKU(s)** BCL-1217-4, BCL-1217-6

### Recommended use of the chemical and restrictions on use

**Recommended Use** No information available.  
**Uses advised against** No information available

### Details of the supplier of the safety data sheet

**Supplier Address**  
Vogel Automotive Coatings  
1020 Albany Place SE  
Orange City, IA 51041  
Phone: 712-737-4993  
Fax: 712-737-4997

### Emergency telephone number

**Emergency Telephone** Chemtrec 1-800-424-9300

## 2. HAZARDS IDENTIFICATION

### Classification

### OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

### Emergency Overview

#### **Danger**

#### **Hazard statements**

Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May cause genetic defects  
May cause cancer  
May cause damage to organs through prolonged or repeated exposure  
May be fatal if swallowed and enters airways  
Highly flammable liquid and vapor

**Appearance** No information available**Physical state** liquid**Odor** No information available**Precautionary Statements - Prevention**

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Use personal protective equipment as required  
 Use only outdoors or in a well-ventilated area  
 Wash face, hands and any exposed skin thoroughly after handling  
 In case of inadequate ventilation wear respiratory protection  
 Contaminated work clothing should not be allowed out of the workplace  
 Wear protective gloves  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation or rash occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician  
 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician  
 Do NOT induce vomiting  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store locked up  
 Store in a well-ventilated place. Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)****Other Information**

- May be harmful if swallowed
- May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
---------------	---------	----------	--------------

Polymeric Isocyanate	28182-81-2	30 - 60	*
Xylene	1330-20-7	10 - 30	*
Acetone	67-64-1	10 - 30	*
Ethyl Benzene	100-41-4	7 - 13	*
Aromatic 100	64742-95-6	5 - 10	*
1,2,4-Trimethylbenzene	95-63-6	1 - 5	*
p-Toluenesulfonyl Isocyanate	4083-64-1	0.1 - 1	*
Cumene	98-82-8	0.1 - 1	*

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.
<b>Eye contact</b>	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician. Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
<b>Skin Contact</b>	Wash off immediately with plenty of water. Call a physician immediately. Wash contaminated clothing before reuse. If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician. Wash contaminated clothing before reuse.
<b>Inhalation</b>	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician immediately. Move to fresh air in case of accidental inhalation of vapors. May cause allergic respiratory reaction.
<b>Ingestion</b>	Do NOT induce vomiting. Rinse mouth. If symptoms persist, call a physician. Drink 1 or 2 glasses of water. Never give anything by mouth to an unconscious person. Clean mouth with water and drink afterwards plenty of water. Call a physician.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required.
<b><u>Most important symptoms and effects, both acute and delayed</u></b>	
<b>Symptoms</b>	May cause allergic skin reaction. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
<b><u>Indication of any immediate medical attention and special treatment needed</u></b>	
<b>Note to physicians</b>	Treat symptomatically. Symptoms may be delayed. May cause sensitization by skin contact. May cause sensitization by inhalation and skin contact.

#### 5. FIRE-FIGHTING MEASURES

##### **Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**Unsuitable extinguishing media** CAUTION: Use of water spray when fighting fire may be inefficient.

##### **Specific hazards arising from the chemical**

Extremely flammable.

**Hazardous combustion products** Carbon monoxide. Carbon dioxide (CO<sub>2</sub>). Nitrogen oxides (NO<sub>x</sub>).

**Explosion data****Sensitivity to Mechanical Impact** None.**Sensitivity to Static Discharge** None.**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.

**Environmental precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system. See Section 12 for additional ecological information.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Pick up and transfer to properly labeled containers. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Cover liquid spill with sand, earth or other non-combustible absorbent material. Soak up with inert absorbent material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Avoid contact with skin, eyes or clothing. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.

**Incompatible materials** Strong acids. Strong oxidizing agents. Chlorinated compounds. Incompatible with oxidizing agents. Strong bases. Water. Alcohols. Amines. Copper.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Control parameters****Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
.			

Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
Acetone 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
Ethyl Benzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
1,2,4-Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m <sup>3</sup>
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m <sup>3</sup> (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

**Other Information**

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

**Appropriate engineering controls**

**Engineering Controls**

Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Tight sealing safety goggles. Face protection shield.

**Skin and body protection**

Wear protective gloves and protective clothing.

**Respiratory protection**

In case of insufficient ventilation, wear suitable respiratory equipment.

**General Hygiene Considerations**

When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

**Physical state**

liquid

**Appearance**

No information available

**Odor**

No information available

**Color**

No information available

**Odor threshold**

No information available

**Property**

**Values**

**Remarks • Method**

**pH**

No information available

**Melting point/freezing point**

No information available

**Boiling point / boiling range**

>= 56 °C / 133 °F

**Flash point**

-17 °C / 1 °F

Evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor pressure	No information available
Vapor density	No information available
Specific Gravity	0.96
Water solubility	No information available
Solubility in other solvents	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available
Explosive properties	No information available
Oxidizing properties	No information available

**Other Information**

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	No information available
Density	8.03 lbs/gal
Bulk density	No information available
Percent solids by weight	43.0%
Percent volatile by weight	41.6%
Percent solids by volume	35.4%
Actual VOC (lbs/gal)	3.3
Actual VOC (grams/liter)	400.5
EPA VOC (lbs/gal)	4.1
EPA VOC (grams/liter)	492.3
EPA VOC (lb/gal solids)	9.4

## 10. STABILITY AND REACTIVITY

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong acids. Strong oxidizing agents. Chlorinated compounds. Incompatible with oxidizing agents. Strong bases. Water. Alcohols. Amines. Copper.

**Hazardous Decomposition Products**

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

**Information on likely routes of exposure**

<b>Product Information</b>	No data available
<b>Inhalation</b>	May cause sensitization by inhalation.

<b>Eye contact</b>	May cause irritation.
<b>Skin Contact</b>	May cause irritation. May cause sensitization by skin contact.
<b>Ingestion</b>	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Polymeric Isocyanate 28182-81-2	-	-	= 18500 mg/m <sup>3</sup> ( Rat ) 1 h
Xylene 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit ) > 1700 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Acetone 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
Ethyl Benzene 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.4 mg/L ( Rat ) 4 h
Aromatic 100 64742-95-6	= 8400 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	= 3400 ppm ( Rat ) 4 h
1,2,4-Trimethylbenzene 95-63-6	= 3280 mg/kg ( Rat )	> 3160 mg/kg ( Rabbit )	= 18 g/m <sup>3</sup> ( Rat ) 4 h
p-Toluenesulfonyl Isocyanate 4083-64-1	= 2234 mg/kg ( Rat )	-	> 640 ppm ( Rat ) 1 h
Cumene 98-82-8	= 1400 mg/kg ( Rat )	= 12300 µL/kg ( Rabbit )	> 3577 ppm ( Rat ) 6 h = 39000 mg/m <sup>3</sup> ( Rat ) 4 h

**Information on toxicological effects**

**Symptoms** No information available.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** May cause sensitization by inhalation and skin contact.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** No information available.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Ethyl Benzene 100-41-4	A3	Group 2B	-	X
Cumene 98-82-8	-	Group 2B	Reasonably Anticipated	X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not classifiable as a human carcinogen

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Chronic toxicity**

Ethylbenzene has been classified by the International Agency for Research on Cancer (IARC) as possibly carcinogenic to humans (Group 2B). Prolonged or repeated overexposure to ethylbenzene may result in adverse effects to the kidneys, liver, respiratory system, thyroid, testicles, and pituitary glands. Avoid repeated exposure. May cause adverse effects on the bone marrow and blood-forming system.

**Target Organ Effects**

blood, Central nervous system, Eyes, Respiratory system, Skin.

**Aspiration hazard**

No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity

Toxic to aquatic life with long lasting effects

43.26% of the mixture consists of component(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Xylene 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 19: 96 h Lepomis macrochirus mg/L LC50 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static	0.6: 48 h Gammarus lacustris mg/L LC50 3.82: 48 h water flea mg/L EC50
Acetone 67-64-1	-	6210 - 8120: 96 h Pimephales promelas mg/L LC50 static 4.74 - 6.33: 96 h Oncorhynchus mykiss mg/L LC50 8300: 96 h Lepomis macrochirus mg/L LC50	10294 - 17704: 48 h Daphnia magna mg/L EC50 Static 12600 - 12700: 48 h Daphnia magna mg/L EC50
Ethyl Benzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 32: 96 h Lepomis macrochirus mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Aromatic 100 64742-95-6	-	9.22: 96 h Oncorhynchus mykiss mg/L LC50	6.14: 48 h Daphnia magna mg/L EC50
1,2,4-Trimethylbenzene 95-63-6	-	7.19 - 8.28: 96 h Pimephales promelas mg/L LC50 flow-through	6.14: 48 h Daphnia magna mg/L EC50
Cumene 98-82-8	2.6: 72 h Pseudokirchneriella subcapitata mg/L EC50	6.04 - 6.61: 96 h Pimephales promelas mg/L LC50 flow-through 2.7: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 5.1: 96 h Poecilia reticulata mg/L LC50 semi-static 4.8: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	0.6: 48 h Daphnia magna mg/L EC50 7.9 - 14.1: 48 h Daphnia magna mg/L EC50 Static

### Persistence and degradability

No information available.

### Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Xylene 1330-20-7	2.77 - 3.15
Acetone 67-64-1	-0.24
Ethyl Benzene 100-41-4	3.2
1,2,4-Trimethylbenzene 95-63-6	3.63



Cumene 98-82-8	3.7
-------------------	-----

**Other adverse effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001 U002 U055 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Acetone 67-64-1	-	Included in waste stream: F039	-	U002
Ethyl Benzene 100-41-4	-	Included in waste stream: F039	-	-
Cumene 98-82-8	-	-	-	U055

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Acetone 67-64-1	Ignitable
Ethyl Benzene 100-41-4	Toxic Ignitable
Cumene 98-82-8	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID no.** UN1263  
**Proper shipping name** Paint Related Material  
**Hazard Class** 3  
**Packing Group** II  
**Special Provisions** 149, B52, IB2, T4, TP1, TP8, TP28  
**Description** UN1263, Paint related material, 3, II,  
**Emergency Response Guide Number** 128

**TDG**

**UN/ID no.** UN1263  
**Proper shipping name** Paint Related Material  
**Hazard Class** 3  
**Packing Group** II  
**Description** UN1263, Paint related material, 3, II

**MEX**

**UN/ID no.** UN1263  
**Proper shipping name** Paint Related Material  
**Hazard Class** 3

**Packing Group** II  
**Description** UN1263, Paint related material, 3, II

**ICAO (air)**

**UN/ID no.** UN1263  
**Proper shipping name** Paint Related Material  
**Hazard Class** 3  
**Packing Group** II  
**Special Provisions** A3, A72  
**Description** UN1263, Paint related material, 3, II

**IATA**

**UN/ID no.** UN1263  
**Proper shipping name** Paint Related Material  
**Hazard Class** 3  
**Packing Group** II  
**ERG Code** 3L  
**Special Provisions** A3, A72  
**Description** UN1263, Paint related material, 3, II

**IMDG**

**UN/ID no.** UN1263  
**Proper shipping name** Paint related material  
**Hazard Class** 3  
**Packing Group** II  
**EmS-No.** F-E, S-E  
**Special Provisions** 163  
**Description** UN1263, Paint related material, 3, II

**RID**

**UN/ID no.** UN1263  
**Proper shipping name** Paint Related Material  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Description** UN1263, Paint related material, 3, II

**ADR**

**UN/ID no.** UN1263  
**Proper shipping name** Paint Related Material  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Tunnel restriction code** (D/E)  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint related material, 3, II, (D/E)  
**Labels** 3

**ADN**

**Proper shipping name** Paint Related Material  
**Hazard Class** 3  
**Packing Group** II  
**Classification code** F1  
**Special Provisions** 163, 640C, 650  
**Description** UN1263, Paint related material , 3, II  
**Hazard label(s)** 3  
**Limited quantity (LQ)** 5 L  
**Ventilation** VE01

<b>15. REGULATORY INFORMATION</b>
-----------------------------------

**International Inventories**

**TSCA** Complies

DSL/NDSL	Complies
EINECS/ELINCS	Complies
ENCS	Does not comply
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Xylene	1.0
Ethyl Benzene	0.1
1,2,4-Trimethylbenzene	1.0

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X
Ethyl Benzene 100-41-4	1000 lb	X	X	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Acetone 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethyl Benzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Cumene 98-82-8	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Ethyl Benzene - 100-41-4	Carcinogen
Cumene - 98-82-8	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts
Xylene 1330-20-7	X	X
Acetone 67-64-1	X	X
Ethyl Benzene 100-41-4	X	X
1,2,4-Trimethylbenzene 95-63-6	X	X
Cumene 98-82-8	X	X

Chemical Name	Pennsylvania
Xylene 1330-20-7	X
Acetone 67-64-1	X
Ethyl Benzene 100-41-4	X
1,2,4-Trimethylbenzene 95-63-6	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**Hazardous air pollutants (HAPS) content**

LIST OF HAZARDOUS AIR POLLUTANTS SUBJECT TO THE PROVISIONS OF THE CLEAN AIR ACT, TITLE I SECTION 112 'National Emission Standards for Hazardous Air Pollutants' (present individually at 1% by weight, or greater):

Chemical Name	Weight % of HAPS in Product	Pounds HAPS / Gal Product
Xylene 1330-20-7	21.17%	1.70
Ethyl Benzene 100-41-4	11.30%	0.91

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Properties -
<b>HMIS</b>	Health hazards 2 *	Flammability 3	Physical hazards 0	Personal protection X

Chronic Hazard Star Legend                      \* = Chronic Health Hazard

Revision Date    03-Feb-2017

Revision Note  
No information available

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

**End of Safety Data Sheet**