SAFETY DATA SHEET

Revision date 28-Aug-2019 **Version** 3 **Supersedes Date:** 19-Aug-2019

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product identifier
Product Code APR12111-1.G01

Product Name 1K PRIMER SURFACER BLACK GL

Other means of identification
No information available

Recommended use of the chemical and restrictions on use
Paint, Coatings

Details of the supplier of the safety data sheet
See section 16 for more information

Manufactured for: Liberty Bell Equipment Corp
810 N. Jefferson Ave.

St. Louis, MO 63106
www.axiscoating.com
888-646-1400

E-mail address No information available

Emergency telephone number
United States of America 1-888-345-5732

Section 2: HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2
Skin sensitization	Category 1B
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 2

Label elements

Signal word **DANGER**

HAZARD STATEMENTS
Highly flammable liquid and vapor
Causes skin irritation
Causes serious eye irritation
May cause an allergic skin reaction
Suspected of causing cancer
Suspected of damaging fertility or the unborn child
May be fatal if swallowed and enters airways
Causes damage to the following organs: optic nerve
May cause damage to the following organs through prolonged or repeated exposure: Nervous System

PREVENTION
Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash face, hands and any exposed skin thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

RESPONSE
IF exposed: Call a POISON CENTER or doctor/physician.

Eyes
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin
If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation
IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Fire
In case of fire: Use CO2, dry chemical, or foam for extinction.

STORAGE
Store locked up. Store in a well-ventilated place. Keep cool.

DISPOSAL
Dispose of contents/containers in accordance with local regulations.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)
No information available.

OTHER HAZARDS
spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	weight-%
Toluene	108-88-3	10 - 25
2-Pentanone, 4-methyl-	108-10-1	10 - 25
Acetone	67-64-1	5 - 10
Isopropyl alcohol	67-63-0	3 - 5
Modified rosin ester	68038-41-5	3 - 5

Xylenes	1330-20-7	1 - 3
Methyl alcohol	67-56-1	1 - 3
Carbon black	1333-86-4	0.3 - 1
Ethylbenzene	100-41-4	0.3 - 1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Section 4: FIRST AID MEASURES

First Aid Measures

General advice
IF exposed: Call a POISON CENTER or doctor/physician.

Eye contact
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact
If skin irritation or rash occurs: Get medical advice/attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower. Wash contaminated clothing before reuse.

Inhalation
IF INHALED: Call a POISON CENTER or doctor if you feel unwell.

Ingestion
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

Suitable extinguishing media
Dry chemical, CO2, water spray or alcohol-resistant foam.

Not to be used for safety reasons: Strong water jet

Specific hazards arising from the chemical
Burning produces heavy smoke. Fire may produce irritating and/or toxic gases. In the event of fire and/or explosion do not breathe fumes. May cause sensitization by skin contact. spontaneously combustible material. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal. Keep product and empty container away from heat and sources of ignition.

Special protective equipment for fire-fighters
Wear self-contained breathing apparatus and protective suit. Cool containers with flooding quantities of water until well after fire is out. Do not allow run-off from fire-fighting to enter drains or water courses.

Section 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions
Avoid breathing vapors or mists. Remove all sources of ignition. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Keep people away from and upwind of spill/leak. Evacuate personnel to safe areas. Take precautionary measures against static discharges.

For emergency responders
Use personal protection recommended in Section 8.

Environmental precautions

Do not allow into any sewer, on the ground or into any body of water. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

Methods and material for containment and cleaning up

Methods for containment
Prevent further leakage or spillage if safe to do so.

Methods for cleaning up
Dispose of waste product or used containers according to local regulations. Clean with detergents. Avoid solvent cleaners. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Take up mechanically, placing in appropriate containers for disposal.

Section 7: HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling
Prevent the creation of flammable or explosive concentrations of vapor in air and avoid vapor concentration higher than the occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Never use pressure to empty container. Comply with the health and safety at work laws. Prevent product from entering drains. Vapors are heavier than air and may spread along floors. Vapors may form explosive mixtures with air. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapors/spray. Use only in well-ventilated areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Risk of self-ignition of used cleaning rags, paper wipes etc. Contaminated materials should be soaked in water and placed in a closed metal container before disposal.

General Hygiene Considerations
When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions
Keep/store only in original container. Store in accordance with local regulations. Keep unauthorized personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place. Keep tightly closed in a dry and cool place.

Incompatible materials
Strong bases. Strong oxidizing agents. Strong reducing agents. Alkali.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits
If S* appears in the OEL table, it indicates this chemical contains a skin notation.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m^3 STEL: 150 ppm STEL: 560 mg/m^3
2-Pentanone, 4-methyl- 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m^3	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m^3 STEL: 75 ppm STEL: 300 mg/m^3
Acetone	STEL: 500 ppm	TWA: 1000 ppm	IDLH: 2500 ppm

67-64-1	TWA: 250 ppm	TWA: 2400 mg/m³	TWA: 250 ppm TWA: 590 mg/m³
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³
Xylenes 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m³	
Methyl alcohol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m³	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 325 mg/m³
Carbon black 1333-86-4	TWA: 3 mg/m³ inhalable particulate matter	TWA: 3.5 mg/m³	IDLH: 1750 mg/m³ TWA: 3.5 mg/m³ TWA: 0.1 mg/m³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³

Appropriate engineering controls

Engineering Controls
Ensure adequate ventilation, especially in confined areas. Provide local exhaust ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection
Tight sealing safety goggles.

Skin and body protection
Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Wear suitable protective clothing. Personnel should wear anti-static clothing made of natural fiber or of high temperature resistant synthetic fiber.

Hand Protection
There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance. Wear protective gloves.

Respiratory protection
When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Thermal Protection
No information available

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	liquid
Appearance	No information available
Odor	Solvent
Color	black
Odor Threshold	No information available
pH value	No information available
Melting point/freezing point	No information available
Boiling point / boiling range	56.05 °C / 133 °F

flash point	-20 °C / -4 °F
evaporation rate	No information available
Flammability (solid, gas)	No information available
Flammability Limit in Air	
Upper flammability limit:	No information available
Lower flammability limit:	No information available
Vapor Pressure	No information available
vapor density	No information available
Density (lbs per US gallon)	9.55
specific gravity	1.14
Solubility(ies)	No information available
Partition coefficient	No information available
Autoignition temperature	No information available
Decomposition temperature	No information available
Kinematic viscosity	No information available
Dynamic viscosity	No information available

Other information

Section 10: STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous polymerization None under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong bases. Strong oxidizing agents. Strong reducing agents. Alkali.

Hazardous Decomposition Products Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx).

Section 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Eye contact
Causes serious eye irritation
Skin Contact
May cause an allergic skin reaction
Causes skin irritation
Ingestion
May be fatal if swallowed and enters airways
Inhalation
Not applicable

Numerical measures of toxicity - Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
2-Pentanone, 4-methyl- 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
Acetone 67-64-1	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³ (Rat) 8 h
Isopropyl alcohol 67-63-0	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	= 72600 mg/m³ (Rat) 4 h
Modified rosin ester 68038-41-5	-	-	-
Xylenes 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 29.08 mg/L (Rat) 4 h

Methyl alcohol 67-56-1	= 6200 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 64000 ppm (Rat) 4 h = 22500 ppm (Rat) 8 h
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5702 Mg/kg
ATEmix (dermal) 11107 Mg/kg
ATEmix (inhalation-dust/mist) 7 mg/l
ATEmix (inhalation-vapor) 49 mg/l

UNKNOWN ACUTE TOXICITY 0% of the mixture consists of ingredient(s) of unknown toxicity.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

According to IARC, Volume 93, no significant exposure to primary particles of carbon black is thought to occur from use in paints since the pigment is bound to other materials.

Chemical Name	ACGIH	IARC	NTP	OSHA
2-Pentanone, 4-methyl- 108-10-1	A3	Group 2B		X
Carbon black 1333-86-4	A3	Group 2B		X
Ethylbenzene 100-41-4	A3	Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen.
IARC (International Agency for Research on Cancer)
Group 2B - Possibly Carcinogenic to Humans.
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present.

Skin corrosion/irritation Causes skin irritation
Serious eye damage/eye irritation Causes serious eye irritation
Skin sensitization May cause an allergic skin reaction
Respiratory sensitization Not applicable
Germ cell mutagenicity Not applicable
Carcinogenicity Suspected of causing cancer
Reproductive Toxicity Suspected of damaging fertility or the unborn child
Specific target organ toxicity (single exposure)
Causes damage to the following organs: optic nerve
Specific target organ toxicity (repeated exposure)
May cause damage to the following organs through prolonged or repeated exposure: Nervous System
Aspiration hazard May be fatal if swallowed and enters airways

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity
Environmental precautions Prevent product from entering drains.

Persistence and degradability
No information available

Bioaccumulation
No information available

Mobility
No information available

Other adverse effects No information available

Section 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated packaging Improper disposal or reuse of this container may be dangerous and illegal. Empty containers must be scrapped or reconditioned.

Section 14: TRANSPORT INFORMATION

	DOT	IMDG	IATA
14.1 UN/ID no	UN1263	UN1263	UN1263
14.2 Proper shipping name	Paint	Paint	Paint
14.3 Hazard Class	3	3	3
14.4 Packing Group	II	II	II
14.5 Environmental hazard			
14.6 Special Provisions	149, B52, IB2, T4, TP1, TP8, TP28, 367	163, 367	A3, A72, A192
	Emergency Response Guide Number 128	**EmS-No** F-E, S-E	

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

Section 15: REGULATORY INFORMATION

International Inventories

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory — All components are listed or exempt from listing.

DSL - Canadian Domestic Substances List — Not all components are listed or exempt from listing

US Federal Regulations

Chemical Name	SARA 313 - Threshold Values %	Metals	Hazardous air pollutants (HAPs) content
Toluene 108-88-3 10 - 25	1		Present
2-Pentanone, 4-methyl- 108-10-1 10 - 25	1		Present
Xylenes 1330-20-7 1 - 3	1		Present
Methyl alcohol 67-56-1 1 - 3	1		Present
Ethylbenzene 100-41-4 0.3 - 1	0.1		Present

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Toluene	1000 lb	X	X	X

108-88-3				
Xylenes 1330-20-7	100 lb			X
Ethylbenzene 100-41-4	1000 lb	X	X	X

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Toluene 108-88-3	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
2-Pentanone, 4-methyl- 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Acetone 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Xylenes 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Methyl alcohol 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

Rule 66 status of product
Photochemically reactive.

California Proposition 65
WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

U.S. EPA Label information
EPA Pesticide registration number Not applicable

U.S. State Right-to-Know Regulations

Chemical Name
Proprietary Inert
Toluene 108-88-3
2-Pentanone, 4-methyl- 108-10-1
Cellulosic Polymer
Acetone 67-64-1
Isopropyl alcohol 67-63-0
Proprietary Non-Hazardous Ingredient - Proprietary CAS
Modified rosin ester 68038-41-5
Xylenes 1330-20-7
Methyl alcohol 67-56-1
Ethylbenzene 100-41-4

Section 16: OTHER INFORMATION

HMIS
Health hazards 4*
** = Chronic Health Hazard*

Flammability	3
Physical hazards	0
Personal Protection	X

Valspar Automotive
600 Nova Drive S.E.
Massillon, OH 44646
330-830-6000

Prepared By Regulatory Department

Revision date 28-Aug-2019
Revision Note No information available

Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

End of Safety Data Sheet