

# SAFETY DATA SHEET.

Issuing date 8/2/2019

Revision Date 8/2/2019

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

**Product identifier**

**Product name**

Total Prime Black

**Product number**

P32, 192-P32

**Recommended use of the**

**chemical and restrictions on use**

For professional and industrial use only. Not for sale to the general public.

**Product Type**

Extremely flammable aerosol

**Synonyms**

None

**Recommended Use**

Primer.

**Uses advised against**

No information available

**Manufacturer/Distributor:**

Transtar Autobody Technologies

2040 Heiserman Drive

Brighton, MI 48116

800-824-2483

**CHEMTREC 24 Hour**

**Emergency Phone Number**

CHEMTREC USA or Canada: 1-800-424-9300

CHEMTREC International +1-703-741-5970

## 2. HAZARDS IDENTIFICATION

### Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive Toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 1
Specific target organ toxicity (repeated exposure)	Category 2
Flammable aerosols	Category 1
Gases under pressure	Compressed Gas

### GHS Label elements, including precautionary statements

#### Emergency Overview

#### DANGER

##### Hazard Statements

Causes skin irritation  
 Causes serious eye irritation  
 Suspected of causing cancer  
 Suspected of damaging fertility or the unborn child  
 Causes damage to organs (Central Nervous System, Peripheral Nervous System, Eyes, Kidney, Liver, Lungs, Respiratory System, Reproductive System, Skin, Central Vascular System and Gastrointestinal Tract.)  
 May cause damage to organs (Central Nervous System, Peripheral Nervous System, Central Vascular System, Eyes, Kidney, Liver, Lungs, Respiratory System, Reproductive System and Skin) through prolonged or repeated exposure.  
 Extremely flammable aerosol  
 Contains gas under pressure; may explode if heated



**Appearance** opaque

**Physical state** Aerosol

**Odor** Solvent

#### Precautionary Statements - Prevention

Obtain special instructions before use  
 Do not handle until all safety precautions have been read and understood  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Wash face, hands and any exposed skin thoroughly after handling  
 Do not breathe dust/fume/gas/mist/vapors/spray  
 Do not eat, drink or smoke when using this product  
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking  
 Do not spray on an open flame or other ignition source  
 Pressurized container: Do not pierce or burn, even after use

#### Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician  
 Specific treatment (see first aid on this label)  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention  
 IF ON SKIN: Wash with plenty of soap and water.  
 If skin irritation occurs: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse

**Precautionary Statements - Storage**

Store locked up  
 Protect from sunlight. Store in a well-ventilated place  
 Do not expose to temperatures exceeding 122°F (50°C)

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

None

**Other information**

0% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %*
ACETONE	67-64-1	30-40
PROPANE/ISOBUTANE/N-BUTANE	68476-86-8	20-30
METHYL ISOBUTYL KETONE	108-10-1	1-10
TALC	14807-96-6	1-10
1-METHOXY-2-PROPANOL ACETATE	108-65-6	1-10
NITROCELLULOSE RESIN	9004-70-0	1-10
XYLENE	1330-20-7	1-10
TOLUENE	108-88-3	1-10
METHANOL	67-56-1	1-10
MALEIC MODIFIED ROSIN RESIN	PROPRIETARY	1-10
ISOPROPYL ALCOHOL	67-63-0	1-10
BUTYL ACETATE	123-86-4	1-10
CARBON BLACK	1333-86-4	0.1-1.0
ETHYL BENZENE	100-41-4	0.1-1.0
ZINC OXIDE	1314-13-2	0.1-1.0

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. FIRST AID MEASURES

**First aid measures for different exposure routes**

<b>General advice</b>	Avoid contact with eyes, skin, and clothing. Avoid breathing vapors mist, or gas.
<b>Eye contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water for at least 15 minutes.
<b>Inhalation</b>	Move to fresh air. If breathing is difficult, give oxygen. Artificial respiration and/or oxygen may be necessary. If breathing has stopped, contact emergency medical services immediately.

**Ingestion** Do NOT induce vomiting. Call a physician immediately. Never give anything by mouth to an unconscious person. Risk of product entering the lungs on vomiting after ingestion.

**Most important symptoms/effects, acute and delayed**

**Main Symptoms** Causes skin and eye irritation . May cause respiratory irritation. May be harmful if swallowed and enters airways.

**Indication of immediate medical attention and special treatment needed, if necessary**

**Notes to physician** Treat symptomatically.

## 5. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media**

water fog. Dry chemical. Carbon dioxide (CO2). Cool containers / tanks with water spray.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Flammable or Extremely Flammable aerosol. Container may burst in fire.

**Explosion Data**

**Sensitivity to Mechanical Impact** none.

**Sensitivity to Static Discharge** Yes.

**Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Use shielding to protect fire-fighters from bursting containers.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Use with adequate ventilation to keep the exposure levels below the OELS.

**Environmental precautions**

**Environmental precautions** Report spills as required by local and federal regulations.

**Methods and materials for containment and cleaning up**

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up**

Pick up and transfer to properly labeled containers. Soak up with inert absorbent material. Clean contaminated surface thoroughly. After cleaning, flush away traces with water. Take precautionary measures against static discharges. Ground and bond containers when transferring material.

## 7. HANDLING AND STORAGE

**Precautions for safe handling**

**Advice on safe handling**

Avoid contact with eyes. Avoid breathing vapors or mists. Contents under pressure. Do not puncture or incinerate cans. Do not stick pin or any other sharp object into opening on top of can. Avoid skin contact. Use with adequate ventilation. Keep container away from heat, flames, and all other sources of ignition. Keep can away from all sources of electricity such as electric motors and batteries. Do not spray on hot surfaces.

**Conditions for safe storage, including any incompatibilities**

<b>Technical measures/Storage conditions</b>	Keep container tightly closed in a dry and well-ventilated place.
<b>Incompatible products</b>	Strong acids, alkalis, or oxidizing agents. Strong oxidizing agents. Acids. Chlorinated compounds. Store away from strong oxidizers and acids.
<b>Aerosol Level</b>	2

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m <sup>3</sup>
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	74-98-6: TWA: 1000 ppm 106-97-8: STEL: 1000 ppm 75-28-5: STEL: 1000 ppm	74-98-6: TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> 106-97-8: (vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m <sup>3</sup>	74-98-6: IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m <sup>3</sup> 106-97-8: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup> 75-28-5: TWA: 800 ppm TWA: 1900 mg/m <sup>3</sup>
METHYL ISOBUTYL KETONE 108-10-1	STEL: 75 ppm TWA: 20 ppm	TWA: 100 ppm TWA: 410 mg/m <sup>3</sup> (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m <sup>3</sup> (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m <sup>3</sup>	IDLH: 500 ppm TWA: 50 ppm TWA: 205 mg/m <sup>3</sup> STEL: 75 ppm STEL: 300 mg/m <sup>3</sup>
TALC 14807-96-6	TWA: 2 mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	(vacated) TWA: 2 mg/m <sup>3</sup> respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	IDLH: 1000 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup> containing no Asbestos and <1% Quartz respirable dust
XYLENE 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m <sup>3</sup>	-
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m <sup>3</sup> (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m <sup>3</sup> Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m <sup>3</sup> STEL: 150 ppm STEL: 560 mg/m <sup>3</sup>
METHANOL 67-56-1	STEL: 250 ppm TWA: 200 ppm Skin - potential significant contribution to overall exposure by the cutaneous route	TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m <sup>3</sup> (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m <sup>3</sup> (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m <sup>3</sup> STEL: 250 ppm STEL: 325 mg/m <sup>3</sup>

ISOPROPYL ALCOHOL 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m <sup>3</sup> (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m <sup>3</sup>	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m <sup>3</sup> STEL: 500 ppm STEL: 1225 mg/m <sup>3</sup>
BUTYL ACETATE 123-86-4	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m <sup>3</sup> (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m <sup>3</sup>	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m <sup>3</sup> STEL: 200 ppm STEL: 950 mg/m <sup>3</sup>
CARBON BLACK 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable fraction	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	IDLH: 1750 mg/m <sup>3</sup> TWA: 3.5 mg/m <sup>3</sup> TWA: 0.1 mg/m <sup>3</sup> Carbon black in presence of Polycyclic aromatic hydrocarbons PAH
ETHYL BENZENE 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m <sup>3</sup> (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m <sup>3</sup>	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m <sup>3</sup> STEL: 125 ppm STEL: 545 mg/m <sup>3</sup>
ZINC OXIDE 1314-13-2	STEL: 10 mg/m <sup>3</sup> respirable fraction TWA: 2 mg/m <sup>3</sup> respirable fraction	TWA: 5 mg/m <sup>3</sup> fume TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 5 mg/m <sup>3</sup> fume (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) STEL: 10 mg/m <sup>3</sup> fume	IDLH: 500 mg/m <sup>3</sup> Ceiling: 15 mg/m <sup>3</sup> dust TWA: 5 mg/m <sup>3</sup> dust and fume STEL: 10 mg/m <sup>3</sup> fume

ACGIH: (American Conference of Governmental Industrial Hygienists)

OSHA: (Occupational Safety & Health Administration)

NIOSH IDLH: Immediately Dangerous to Life or Health

#### Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

#### Exposure controls

##### Engineering Measures

Ventilation systems. Use adequate ventilation to keep the exposure levels below the OELs.

#### Individual protection measures, such as personal protective equipment

##### Eye/Face Protection

Safety glasses with side-shields.

##### Skin and body protection

Chemical resistant apron. Protective gloves.

##### Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

#### Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Physical and chemical properties

Physical state  
Appearance  
Color

Aerosol  
opaque  
black

Odor  
Odor Threshold

Solvent

<u>Property</u>	<u>Values</u>	<u>Remarks • Methods</u>
pH	No information available	
Melting/freezing point	No information available	
Boiling point/boiling range	No information available	
Flash Point	-96.4 °C / -141 °F	Based on propellant
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit	No information available	
lower flammability limit	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Specific Gravity	0.871	
Water solubility	Practically insoluble	
Partition coefficient: n-octanol/water		
Autoignition temperature	No information available	Not applicable
Decomposition temperature		
Viscosity	No information available	
Explosive properties		
<b><u>Other information</u></b>		
VOC Content(%)	43.98	
MIR Value	0.94	
MIR Coating Category	ABP (Auto body primers) MIR <1.55 ABP MIR CHANGES TO <0.95 1/1/17.	

## 10. STABILITY AND REACTIVITY

### Reactivity

No data available

### Chemical stability

Stable under recommended storage conditions.

### Possibility of hazardous reactions

None under normal processing.

### Conditions to Avoid

Heat, flames and sparks.

### Incompatible Materials

Strong acids, alkalis, or oxidizing agents. Strong oxidizing agents. Acids. Chlorinated compounds. Store away from strong oxidizers and acids.

### Hazardous Decomposition Products

Carbon oxides.

## 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	Avoid inhaling vapors or mists. Vapors may irritate throat and respiratory system. May cause drowsiness and dizziness based on components.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin . Prolonged skin contact may defat the skin and produce dermatitis.

**Ingestion**

May be fatal if swallowed and enters airways. Aspiration into the lungs during swallowing may cause serious lung damage which may be fatal.

**Component Information**

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	-	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	= 8.2 mg/L ( Rat ) 4 h
1-METHYOXY-2-PROPANOL ACETATE 108-65-6	= 8532 mg/kg ( Rat )	> 5 g/kg ( Rabbit )	-
NITROCELLULOSE RESIN 9004-70-0	> 5 g/kg ( Rat )	-	-
XYLENE 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h
TOLUENE 108-88-3	= 2600 mg/kg ( Rat )	= 12000 mg/kg ( Rabbit )	= 12.5 mg/L ( Rat ) 4 h
METHANOL 67-56-1	= 6200 mg/kg ( Rat )	-	= 22500 ppm ( Rat ) 8 h
ISOPROPYL ALCOHOL 67-63-0	= 1870 mg/kg ( Rat )	= 4059 mg/kg ( Rabbit )	= 72600 mg/m <sup>3</sup> ( Rat ) 4 h
BUTYL ACETATE 123-86-4	= 10768 mg/kg ( Rat )	> 17600 mg/kg ( Rabbit )	= 390 ppm ( Rat ) 4 h
CARBON BLACK 1333-86-4	> 15400 mg/kg ( Rat )	-	-
ETHYL BENZENE 100-41-4	= 3500 mg/kg ( Rat )	= 15400 mg/kg ( Rabbit )	= 17.2 mg/L ( Rat ) 4 h
ZINC OXIDE 1314-13-2	> 5000 mg/kg ( Rat )	-	-

**Information on toxicological effects****Symptoms**

May cause skin, eye, and respiratory irritation. May be harmful if swallowed and enters airways.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure****Skin corrosion/irritation**

Irritating to skin .

**Eye damage/irritation**

Irritating to eyes.

**Sensitization**

no data available.

**Germ Cell Mutagenicity**

Not a germ cell mutagen.

**Carcinogenicity**

The table below indicates whether each agency has evaluated a listed ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
METHYL ISOBUTYL KETONE 108-10-1	A3	Group 2B	-	-
TALC 14807-96-6	-	Group 2B -Talc based body powder for perineal dusting -possibly carcinogenic to humans	-	-
NITROCELLULOSE RESIN 9004-70-0	-	Group 2A	-	X
CARBON BLACK 1333-86-4	A3	Group 2B	-	-
ETHYL BENZENE 100-41-4	A3	Group 2B	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 2A - Probably Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans



OSHA: (Occupational Safety & Health Administration)

X - Present

<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.
<b>Specific target organ systemic toxicity (single exposure)</b>	Causes damage to Target Organs listed below.
<b>Specific target organ systemic toxicity (repeated exposure)</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Chronic toxicity</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Chronic hydrocarbon abuse has been associated with irregular heart rhythms and potential cardiac arrest. Prolonged skin contact may defat the skin and produce dermatitis. May cause adverse liver effects.
<b>Target Organ Effects</b>	Central Nervous System (CNS), Eyes, Kidney, Liver, Respiratory system, Skin, Central Vascular System (CVS), Gastrointestinal tract (GI), Lungs.
<b>Neurological effects</b>	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.
<b>Aspiration hazard</b>	Not applicable.

#### Numerical measures of toxicity - Product Information

**Unknown Acute Toxicity** 0% of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	4303 mg/kg
<b>ATEmix (dermal)</b>	9407 mg/kg
<b>ATEmix (inhalation-gas)</b>	1832066 mg/l
<b>ATEmix (inhalation-dust/mist)</b>	8.9 mg/l
<b>ATEmix (inhalation-vapor)</b>	21435 mg/l

## 12. ECOLOGICAL INFORMATION

#### Ecotoxicity

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
ACETONE 67-64-1	-	4.74 - 6.33 mL/L LC50 Oncorhynchus mykiss 96h 6210 - 8120 mg/L LC50 Pimephales promelas 96h static 8300 mg/L LC50 Lepomis macrochirus 96h	-	10294 - 17704 mg/L EC50 Daphnia magna 48h Static 12600 - 12700 mg/L EC50 Daphnia magna 48h
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	-	-	-	-
METHYL ISOBUTYL KETONE 108-10-1	400 mg/L EC50 Pseudokirchneriella subcapitata 96h	496 - 514 mg/L LC50 Pimephales promelas 96h flow-through	-	170 mg/L EC50 Daphnia magna 48h
TALC 14807-96-6	-	100 g/L LC50 Brachydanio rerio 96h semi-static	-	-
1-METHOXY-2-PROPANOL ACETATE 108-65-6	-	161 mg/L LC50 Pimephales promelas 96h static	-	500 mg/L EC50 Daphnia magna 48h

XYLENE 1330-20-7	-	13.4 mg/L LC50 Pimephales promelas 96h flow-through 2.661 - 4.093 mg/L LC50 Oncorhynchus mykiss 96h static 13.5 - 17.3 mg/L LC50 Oncorhynchus mykiss 96h 13.1 - 16.5 mg/L LC50 Lepomis macrochirus 96h flow-through 19 mg/L LC50 Lepomis macrochirus 96h 7.711 - 9.591 mg/L LC50 Lepomis macrochirus 96h static 23.53 - 29.97 mg/L LC50 Pimephales promelas 96h static 780 mg/L LC50 Cyprinus carpio 96h semi-static 780 mg/L LC50 Cyprinus carpio 96h 30.26 - 40.75 mg/L LC50 Poecilia reticulata 96h static	-	3.82 mg/L EC50 water flea 48h 0.6 mg/L LC50 Gammarus lacustris 48h
TOLUENE 108-88-3	433 mg/L EC50 Pseudokirchneriella subcapitata 96h 12.5 mg/L EC50 Pseudokirchneriella subcapitata 72h static	15.22 - 19.05 mg/L LC50 Pimephales promelas 96h flow-through 12.6 mg/L LC50 Pimephales promelas 96h static 5.89 - 7.81 mg/L LC50 Oncorhynchus mykiss 96h flow-through 14.1 - 17.16 mg/L LC50 Oncorhynchus mykiss 96h static 5.8 mg/L LC50 Oncorhynchus mykiss 96h semi-static 11.0 - 15.0 mg/L LC50 Lepomis macrochirus 96h static 54 mg/L LC50 Oryzias latipes 96h static 28.2 mg/L LC50 Poecilia reticulata 96h semi-static 50.87 - 70.34 mg/L LC50 Poecilia reticulata 96h static	-	5.46 - 9.83 mg/L EC50 Daphnia magna 48h Static 11.5 mg/L EC50 Daphnia magna 48h
METHANOL 67-56-1	-	28200 mg/L LC50 Pimephales promelas 96h flow-through 100 mg/L LC50 Pimephales promelas 96h static 19500 - 20700 mg/L LC50 Oncorhynchus mykiss 96h flow-through 18 - 20 mL/L LC50 Oncorhynchus mykiss 96h static 13500 - 17600 mg/L LC50 Lepomis macrochirus 96h flow-through	-	-
ISOPROPYL ALCOHOL 67-63-0	1000 mg/L EC50 Desmodemus subspicatus 96h 1000 mg/L EC50 Desmodemus subspicatus 72h	9640 mg/L LC50 Pimephales promelas 96h flow-through 11130 mg/L LC50 Pimephales promelas 96h static 1400000 µg/L LC50 Lepomis macrochirus 96h	-	13299 mg/L EC50 Daphnia magna 48h
BUTYL ACETATE 123-86-4	674.7 mg/L EC50 Desmodemus subspicatus 72h	100 mg/L LC50 Lepomis macrochirus 96h static 17 - 19 mg/L LC50 Pimephales promelas 96h flow-through	-	-

ETHYL BENZENE 100-41-4	4.6 mg/L EC50 Pseudokirchneriella subcapitata 72h 438 mg/L EC50 Pseudokirchneriella subcapitata 96h 2.6 - 11.3 mg/L EC50 Pseudokirchneriella subcapitata 72h static 1.7 - 7.6 mg/L EC50 Pseudokirchneriella subcapitata 96h static	11.0 - 18.0 mg/L LC50 Oncorhynchus mykiss 96h static 4.2 mg/L LC50 Oncorhynchus mykiss 96h semi-static 7.55 - 11 mg/L LC50 Pimephales promelas 96h flow-through 32 mg/L LC50 Lepomis macrochirus 96h static 9.1 - 15.6 mg/L LC50 Pimephales promelas 96h static 9.6 mg/L LC50 Poecilia reticulata 96h static	-	1.8 - 2.4 mg/L EC50 Daphnia magna 48h
---------------------------	--	---	---	--

**Persistence and degradability**

**Bioaccumulation**

Chemical Name	log Pow
ACETONE 67-64-1	-0.24
PROPANE/ISOBUTANE/N-BUTANE 68476-86-8	<=2.8
METHYL ISOBUTYL KETONE 108-10-1	1.19
1-METHOXY-2-PROPANOL ACETATE 108-65-6	0.43
XYLENE 1330-20-7	2.77 - 3.15
TOLUENE 108-88-3	2.7
METHANOL 67-56-1	-0.77
ISOPROPYL ALCOHOL 67-63-0	0.05
BUTYL ACETATE 123-86-4	1.81
ETHYL BENZENE 100-41-4	3.2

**Other adverse effects** No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment**

**Waste Disposal Methods** Dispose of in accordance with federal, state, and local regulations. This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not re-use empty containers.

**14. TRANSPORT INFORMATION**

**DOT Ground** CONSUMER COMMODITY ORM-D  
or  
LIMITED QUANTITY

IATA UN1950, AEROSOLS, FLAMMABLE, 2.1, LTD. QTY.

IMDG UN1950, AEROSOLS, 2.1,LTD.QTY.

### 15. REGULATORY INFORMATION

#### International Inventories

Chemical Name	TSCA	DSL/NDSL	EINECS/ELI NCS	ENCS	IECSC	KECL	PICCS	AICS
ACETONE	X	X	X	X	X	X	X	X
PROPANE/ISOBUTANE/N-BUTANE	X	X	X	Not listed	X	X	X	X
METHYL ISOBUTYL KETONE	X	X	X	X	X	X	X	X
TALC	X	X	X	X	X	X	X	X
1-METHOXY-2-PROPANOL ACETATE	X	X	X	X	X	X	X	X
NITROCELLULOSE RESIN	X	X	Not listed	X	X	X	X	X
XYLENE	X	X	X	X	X	X	X	X
TOLUENE	X	X	X	X	X	X	X	X
METHANOL	X	X	X	X	X	X	X	X
ISOPROPYL ALCOHOL	X	X	X	X	X	X	X	X
BUTYL ACETATE	X	X	X	X	X	X	X	X
CARBON BLACK	X	X	X	X	X	X	X	X
ETHYL BENZENE	X	X	X	X	X	X	X	X
ZINC OXIDE	X	X	X	X	X	X	X	X

#### Legend:

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**CHINA** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

#### U.S. Federal Regulations

##### SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %*	SARA 313 - Threshold Values %
METHYL ISOBUTYL KETONE - 108-10-1	108-10-1	1-10	1.0
TOLUENE - 108-88-3	108-88-3	1-10	1.0
METHANOL - 67-56-1	67-56-1	1-10	1.0
ISOPROPYL ALCOHOL - 67-63-0	67-63-0	1-10	1.0
XYLENE - 1330-20-7	1330-20-7	1-10	1.0
ETHYL BENZENE - 100-41-4	100-41-4	0.1-1.0	0.1
ZINC OXIDE - 1314-13-2	1314-13-2	0.1-1.0	1.0

#### SARA 311/312 Hazard Categories

Acute Health Hazard

Yes

Chronic Health Hazard	Yes
Fire Hazard	Yes
Sudden Release of Pressure Hazard	Yes
Reactive Hazard	no

**Clean Water Act**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb			X
TOLUENE 108-88-3	1000 lb	X	X	X
BUTYL ACETATE 123-86-4	5000 lb			X
ETHYL BENZENE 100-41-4	1000 lb	X	X	X
ZINC OXIDE 1314-13-2		X		

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
ACETONE 67-64-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
XYLENE 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
TOLUENE 108-88-3	1000 lb 1 lb		RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
METHANOL 67-56-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
BUTYL ACETATE 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ

**U.S. State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical Name	California Prop. 65
METHANOL - 67-56-1	Developmental
CARBON BLACK - 1333-86-4	Cancer

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
ACETONE 67-64-1	X	X	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X
TALC 14807-96-6	X	X	X
NITROCELLULOSE RESIN 9004-70-0	X	X	X

XYLENE 1330-20-7	X	X	X
TOLUENE 108-88-3	X	X	X
METHANOL 67-56-1	X	X	X
ISOPROPYL ALCOHOL 67-63-0	X	X	X
BUTYL ACETATE 123-86-4	X	X	X
CARBON BLACK 1333-86-4	X	X	X
ETHYL BENZENE 100-41-4	X	X	X
ZINC OXIDE 1314-13-2	X	X	X

EPA Pesticide Registration Number Not applicable

#### Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

#### **WHMIS Hazard Class**

D2A Very toxic materials

D2B Toxic materials

#### **Legend**

NPRI - National Pollutant Release Inventory

### 16. OTHER INFORMATION

<b>NFPA</b>	Health Hazard 2	Flammability 4	Instability 0	Physical and chemical hazards -
<b>HMIS</b>	Health Hazard 2*	Flammability 4	Physical Hazard 1	Personal protection B

Prepared By Transtar Autobody Technologies

Issuing date 8/2/2019

Revision Date 8/2/2019

#### **Revision Note**

(M)SDS sections updated

#### **Disclaimer**

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

**End of Safety Data Sheet**