



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** FAST LOW VOC CLEAR 1:1 ACTIVATOR

**Other means of identification**

**Product code** BCL1522

**Recommended use** Activator

**Recommended restrictions** No other uses are advised.

### Manufacturer/Importer/Supplier/Distributor information

#### Manufacturer

**Company name** Liberty Bell Equipment Corp.  
**Address** 810 N. Jefferson Ave.  
St. Louis, MO 63106  
United States  
**Telephone** (888) 646-1400

**Website** [www.axiscoatings.com](http://www.axiscoatings.com)

**Emergency phone number** EMERGENCY 24 Hrs. ChemTrec 800-424-9300

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable liquids	Category 2
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 3
	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 2A
	Sensitization, respiratory	Category 1
	Sensitization, skin	Category 1
	Germ cell mutagenicity	Category 1B
	Carcinogenicity	Category 1B
	Reproductive toxicity	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
Specific target organ toxicity, repeated exposure	Category 1	
Aspiration hazard	Category 1	
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

#### Label elements



**Signal word** Danger

**Hazard statement** Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention**

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

**Response**

If swallowed: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. If experiencing respiratory symptoms: Call a poison center/doctor. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish. Collect spillage.

**Storage**

Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**Supplemental information**

100% of the mixture consists of component(s) of unknown acute oral toxicity. 100% of the mixture consists of component(s) of unknown acute dermal toxicity. 100% of the mixture consists of component(s) of unknown acute inhalation toxicity. 100% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 100% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

**3. Composition/information on ingredients**

**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Hexamethylene Diisocyanate		28182-81-2	561.6
Toluene		108-88-3	390.91
BENZENE, M-DIMETHYL-		108-38-3	166.53
BENZENE, P-DIMETHYL-		106-42-3	70 - < 80
BUTYL ACETATE		123-86-4	60 - < 70
ETHYLBENZENE		100-41-4	60 - < 70
BENZENE, O-DIMETHYL		95-47-6	50 - < 60
Solvent Naphtha, petroleum, light aromatic		64742-95-6	5 - 15
Isophorone Diisocyanate Regulatory		4098-71-9	0 - < 1
Methyl Acetate		79-20-9	< 0.1

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

**4. First-aid measures**

**Inhalation**

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a poison center or doctor/physician.

**Skin contact**

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
<b>Most important symptoms/effects, acute and delayed</b>	Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Abdominal pain. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

## 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Water fog. Alcohol resistant foam. Carbon dioxide (CO <sub>2</sub> ). Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Water. Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. This liquid may accumulate static electricity when filling properly grounded containers. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water. During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	Highly flammable liquid and vapor.

## 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
<b>Methods and materials for containment and cleaning up</b>	Use water spray to reduce vapors or divert vapor cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools. Prevent entry into waterways, sewer, basements or confined areas.  Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.  Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.  Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

## Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

## 7. Handling and storage

### Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

For additional information on equipment bonding and grounding, refer to the Canadian Electrical Code in Canada, (CSA C22.1), or the American Petroleum Institute (API) Recommended Practice 2003, "Protection Against Ignitions Arising out of Static, Lightning, and Stray Currents" or National Fire Protection Association (NFPA) 77, "Recommended Practice on Static Electricity" or National Fire Protection Association (NFPA) 70, "National Electrical Code".

### Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Eliminate sources of ignition. Avoid spark promoters. Ground/bond container and equipment. These alone may be insufficient to remove static electricity. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
BENZENE, M-DIMETHYL- (CAS 108-38-3)	PEL	435 mg/m3 100 ppm
BENZENE, O-DIMETHYL (CAS 95-47-6)	PEL	435 mg/m3 100 ppm
BENZENE, P-DIMETHYL- (CAS 106-42-3)	PEL	435 mg/m3 100 ppm
BUTYL ACETATE (CAS 123-86-4)	PEL	710 mg/m3 150 ppm
ETHYLBENZENE (CAS 100-41-4)	PEL	435 mg/m3 100 ppm
Methyl Acetate (CAS 79-20-9)	PEL	610 mg/m3 200 ppm

#### US. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm

**US. OSHA Table Z-2 (29 CFR 1910.1000)**

<b>Components</b>	<b>Type</b>	<b>Value</b>
	TWA	200 ppm

**US. ACGIH Threshold Limit Values**

<b>Components</b>	<b>Type</b>	<b>Value</b>
BENZENE, M-DIMETHYL- (CAS 108-38-3)	STEL	150 ppm
	TWA	100 ppm
BENZENE, O-DIMETHYL (CAS 95-47-6)	STEL	150 ppm
	TWA	100 ppm
BENZENE, P-DIMETHYL- (CAS 106-42-3)	STEL	150 ppm
	TWA	100 ppm
BUTYL ACETATE (CAS 123-86-4)	STEL	150 ppm
	TWA	50 ppm
ETHYLBENZENE (CAS 100-41-4)	TWA	20 ppm
Isophorone Diisocyanate Regulatory (CAS 4098-71-9)	TWA	0.005 ppm
Methyl Acetate (CAS 79-20-9)	STEL	250 ppm
	TWA	200 ppm
Toluene (CAS 108-88-3)	TWA	20 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

<b>Components</b>	<b>Type</b>	<b>Value</b>
BENZENE, M-DIMETHYL- (CAS 108-38-3)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm
BENZENE, O-DIMETHYL (CAS 95-47-6)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm
BENZENE, P-DIMETHYL- (CAS 106-42-3)	STEL	655 mg/m3
		150 ppm
	TWA	435 mg/m3
		100 ppm
BUTYL ACETATE (CAS 123-86-4)	STEL	950 mg/m3
		200 ppm
	TWA	710 mg/m3
		150 ppm
ETHYLBENZENE (CAS 100-41-4)	STEL	545 mg/m3
		125 ppm
	TWA	435 mg/m3
		100 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value
Isophorone Diisocyanate Regulatory (CAS 4098-71-9)	STEL	0.18 mg/m <sup>3</sup>
		0.02 ppm
	TWA	0.045 mg/m <sup>3</sup> 0.005 ppm
Methyl Acetate (CAS 79-20-9)	STEL	760 mg/m <sup>3</sup>
		250 ppm
	TWA	610 mg/m <sup>3</sup> 200 ppm
Toluene (CAS 108-88-3)	STEL	560 mg/m <sup>3</sup>
		150 ppm
	TWA	375 mg/m <sup>3</sup> 100 ppm

**Biological limit values**
**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
BENZENE, M-DIMETHYL- (CAS 108-38-3)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, O-DIMETHYL (CAS 95-47-6)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
BENZENE, P-DIMETHYL- (CAS 106-42-3)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*
ETHYLBENZENE (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*

\* - For sampling details, please see the source document.

**Exposure guidelines**
**US - California OELs: Skin designation**

Isophorone Diisocyanate Regulatory (CAS 4098-71-9) Can be absorbed through the skin.  
Toluene (CAS 108-88-3) Can be absorbed through the skin.

**US - Minnesota Haz Subs: Skin designation applies**

Isophorone Diisocyanate Regulatory (CAS 4098-71-9) Skin designation applies.  
Toluene (CAS 108-88-3) Skin designation applies.

**US - Tennessee OELs: Skin designation**

Isophorone Diisocyanate Regulatory (CAS 4098-71-9) Can be absorbed through the skin.

**US NIOSH Pocket Guide to Chemical Hazards: Skin designation**

Isophorone Diisocyanate Regulatory (CAS 4098-71-9) Can be absorbed through the skin.

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment**
**Eye/face protection**

Chemical respirator with organic vapor cartridge and full facepiece.

<b>Skin protection</b>	
<b>Hand protection</b>	Wear appropriate chemical resistant gloves.
<b>Other</b>	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
<b>Respiratory protection</b>	Chemical respirator with organic vapor cartridge and full facepiece.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.



**General hygiene considerations**

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

**Appearance**

<b>Physical state</b>	Liquid.
<b>Form</b>	Liquid.
<b>Color</b>	Colorless
<b>Odor</b>	Solvent.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-144.4 °F (-98 °C) estimated
<b>Initial boiling point and boiling range</b>	132.4 °F (55.78 °C) estimated
<b>Flash point</b>	3.9 °F (-15.6 °C) estimated
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	1.1 % estimated
<b>Flammability limit - upper (%)</b>	7 % estimated
<b>Explosive limit - lower (%)</b>	Not available.
<b>Explosive limit - upper (%)</b>	Not available.
<b>Vapor pressure</b>	17.4 hPa estimated
<b>Vapor density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	608 °F (320 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Other information</b>	
<b>Density</b>	0.98 g/cm <sup>3</sup> estimated
<b>Explosive properties</b>	Not explosive.
<b>Flammability class</b>	Flammable IB estimated
<b>Oxidizing properties</b>	Not oxidizing.
<b>Percent volatile</b>	70 w/w % By Weight

**Specific gravity** 73.24 v/v % By Volume  
0.98 estimated

## 10. Stability and reactivity

**Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.  
**Chemical stability** Material is stable under normal conditions.  
**Possibility of hazardous reactions** Hazardous polymerization does not occur.  
**Conditions to avoid** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.  
**Incompatible materials** Strong acids. Strong oxidizing agents. Nitrates.  
**Hazardous decomposition products** No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

**Inhalation** Toxic if inhaled. May cause drowsiness and dizziness. Headache. Nausea, vomiting. May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
**Skin contact** Causes skin irritation. May cause an allergic skin reaction.  
**Eye contact** Causes serious eye irritation.  
**Ingestion** Harmful if swallowed. Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia.

**Symptoms related to the physical, chemical and toxicological characteristics** Aspiration may cause pulmonary edema and pneumonitis. May cause drowsiness and dizziness. Headache. Nausea, vomiting. Abdominal pain. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Toxic if inhaled.

Components	Species	Test Results
------------	---------	--------------

BENZENE, M-DIMETHYL- (CAS 108-38-3)

**Acute**

**Dermal**

LD50	Rabbit	12100 mg/kg
------	--------	-------------

**Oral**

LD50	Rat	4300 mg/kg
------	-----	------------

BENZENE, O-DIMETHYL (CAS 95-47-6)

**Acute**

**Dermal**

LD50	Rabbit	> 43 g/kg
------	--------	-----------

BENZENE, P-DIMETHYL- (CAS 106-42-3)

**Acute**

**Dermal**

LD50	Rabbit	> 43 g/kg
------	--------	-----------

BUTYL ACETATE (CAS 123-86-4)

**Acute**

**Inhalation**

LC50	Wistar rat	160 mg/l, 4 Hours
------	------------	-------------------

**Oral**

LD50	Rat	14000 mg/kg
------	-----	-------------

ETHYLBENZENE (CAS 100-41-4)

**Acute**

**Dermal**

LD50	Rabbit	17800 mg/kg
------	--------	-------------



Components	Species	Test Results
<b>Oral</b> LD50	Rat	3500 mg/kg
Isophorone Diisocyanate Regulatory (CAS 4098-71-9)		
<b>Acute</b> <b>Dermal</b> LD50	Rat	1060 mg/kg
<b>Oral</b> LD50	Rat	> 1000 mg/kg
Methyl Acetate (CAS 79-20-9)		
<b>Acute</b> <b>Oral</b> LD50	Rabbit	3.7 g/kg
Toluene (CAS 108-88-3)		
<b>Acute</b> <b>Dermal</b> LD50	Rabbit	12120 mg/kg
<b>Oral</b> LD50	Rat	2.6 g/kg
<b>Skin corrosion/irritation</b>	Causes skin irritation.	
<b>Serious eye damage/eye irritation</b>	Causes serious eye irritation.	
<b>Respiratory or skin sensitization</b>		
<b>Respiratory sensitization</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
<b>Skin sensitization</b>	May cause an allergic skin reaction.	
<b>Germ cell mutagenicity</b>	May cause genetic defects.	
<b>Carcinogenicity</b>	May cause cancer.	
<b>IARC Monographs. Overall Evaluation of Carcinogenicity</b>		
BENZENE, M-DIMETHYL- (CAS 108-38-3)	3 Not classifiable as to carcinogenicity to humans.	
BENZENE, O-DIMETHYL (CAS 95-47-6)	3 Not classifiable as to carcinogenicity to humans.	
BENZENE, P-DIMETHYL- (CAS 106-42-3)	3 Not classifiable as to carcinogenicity to humans.	
ETHYLBENZENE (CAS 100-41-4)	2B Possibly carcinogenic to humans.	
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.	
<b>OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)</b>		
Not regulated.		
<b>US. National Toxicology Program (NTP) Report on Carcinogens</b>		
Not listed.		
<b>Reproductive toxicity</b>	Suspected of damaging fertility or the unborn child.	
<b>Specific target organ toxicity - single exposure</b>	May cause drowsiness and dizziness.	
<b>Specific target organ toxicity - repeated exposure</b>	Causes damage to organs through prolonged or repeated exposure.	
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.	
<b>Chronic effects</b>	Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.	

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
BENZENE, M-DIMETHYL- (CAS 108-38-3)		
<b>Aquatic</b> Crustacea	EC50 Water flea (Daphnia magna)	2.81 - 5 mg/l, 48 hours

Components		Species	Test Results
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.4 mg/l, 96 hours
<b>BENZENE, O-DIMETHYL (CAS 95-47-6)</b>			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	0.78 - 2.51 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	5.59 - 11.6 mg/l, 96 hours
<b>BENZENE, P-DIMETHYL- (CAS 106-42-3)</b>			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	3.55 - 6.31 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	2.6 mg/l, 96 hours
<b>BUTYL ACETATE (CAS 123-86-4)</b>			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	17 - 19 mg/l, 96 hours
<b>ETHYLBENZENE (CAS 100-41-4)</b>			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	1.37 - 4.4 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	7.5 - 11 mg/l, 96 hours
<b>Methyl Acetate (CAS 79-20-9)</b>			
<b>Aquatic</b>			
Fish	LC50	Fathead minnow (Pimephales promelas)	295 - 348 mg/l, 96 hours
<b>Toluene (CAS 108-88-3)</b>			
<b>Aquatic</b>			
Crustacea	EC50	Water flea (Daphnia magna)	5.46 - 9.83 mg/l, 48 hours
Fish	LC50	Coho salmon,silver salmon (Oncorhynchus kisutch)	8.11 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**Bioaccumulative potential**

**Partition coefficient n-octanol / water (log Kow)**

BENZENE, M-DIMETHYL-	3.2
BENZENE, O-DIMETHYL	3.12
BENZENE, P-DIMETHYL-	3.15
BUTYL ACETATE	1.78
ETHYLBENZENE	3.15
Methyl Acetate	0.18
Toluene	2.73

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

### 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F  
The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**US RCRA Hazardous Waste U List: Reference**

BENZENE, M-DIMETHYL- (CAS 108-38-3)	U239
Toluene (CAS 108-88-3)	U220

<b>Waste from residues / unused products</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

The following transportation information is provided based on the manufacturer's interpretation of shipping regulations. Each shipper is responsible for identifying, naming, marking, and labeling prior to offering for transport.

<b>DOT</b>	
<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material including paint thinning, drying, removing, or reducing compound
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	3
<b>Packing group</b>	II
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	149, B52, IB2, T4, TP1, TP8, TP28
<b>Packaging exceptions</b>	150
<b>Packaging non bulk</b>	173
<b>Packaging bulk</b>	242
<b>IATA</b>	
<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	Paint related material (including paint thinning or reducing compounds)
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Other information</b>	
<b>Passenger and cargo aircraft</b>	Allowed with restrictions.
<b>Cargo aircraft only</b>	Allowed with restrictions.
<b>IMDG</b>	
<b>UN number</b>	UN1263
<b>UN proper shipping name</b>	PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning or reducing compound), MARINE POLLUTANT
<b>Transport hazard class(es)</b>	
<b>Class</b>	3
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	Yes
<b>EmS</b>	F-E, <u>S</u> -E
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b>	Not established.

DOT



IATA; IMDG



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

## 15. Regulatory information

**US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

BENZENE, M-DIMETHYL- (CAS 108-38-3)	Listed.
BENZENE, O-DIMETHYL (CAS 95-47-6)	Listed.
BENZENE, P-DIMETHYL- (CAS 106-42-3)	Listed.
BUTYL ACETATE (CAS 123-86-4)	Listed.
ETHYLBENZENE (CAS 100-41-4)	Listed.
Methyl Acetate (CAS 79-20-9)	Listed.
Toluene (CAS 108-88-3)	Listed.

**SARA 304 Emergency release notification**

ISOPHORONE DIISOCYANATE (CAS 4098-71-9) 500 LBS

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)****SARA 302 Extremely hazardous substance**

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
Isophorone Diisocyanate Regulatory	4098-71-9	500	500		

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Acute toxicity (any route of exposure)  
Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitization  
Germ cell mutagenicity  
Carcinogenicity  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Aspiration hazard  
Hazard not otherwise classified (HNOC)

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
BENZENE, M-DIMETHYL-	108-38-3	166.53
BENZENE, O-DIMETHYL	95-47-6	50 - < 60
BENZENE, P-DIMETHYL-	106-42-3	70 - < 80
ETHYLBENZENE	100-41-4	60 - < 70
Isophorone Diisocyanate Regulatory	4098-71-9	0 - < 1
Toluene	108-88-3	390.91

**Other federal regulations****Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

BENZENE, M-DIMETHYL- (CAS 108-38-3)  
BENZENE, O-DIMETHYL (CAS 95-47-6)  
BENZENE, P-DIMETHYL- (CAS 106-42-3)  
ETHYLBENZENE (CAS 100-41-4)  
Toluene (CAS 108-88-3)

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Contains component(s) regulated under the Safe Drinking Water Act.

**Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number**

Toluene (CAS 108-88-3) 6594

**Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))**

Toluene (CAS 108-88-3) 35 %WV

**DEA Exempt Chemical Mixtures Code Number**

Toluene (CAS 108-88-3) 594

**FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace**

BUTYL ACETATE (CAS 123-86-4) Low priority  
Methyl Acetate (CAS 79-20-9) Low priority

**US state regulations****California Proposition 65**

**WARNING:** This product can expose you to ETHYLBENZENE, which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ETHYLBENZENE (CAS 100-41-4) Listed: June 11, 2004

**California Proposition 65 - CRT: Listed date/Developmental toxin**

Toluene (CAS 108-88-3) Listed: January 1, 1991

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

BENZENE, M-DIMETHYL- (CAS 108-38-3)  
BENZENE, O-DIMETHYL (CAS 95-47-6)  
BENZENE, P-DIMETHYL- (CAS 106-42-3)  
ETHYLBENZENE (CAS 100-41-4)  
Isophorone Diisocyanate Regulatory (CAS 4098-71-9)  
Solvent Naphtha, petroleum, light aromatic (CAS 64742-95-6)  
Toluene (CAS 108-88-3)

**International Inventories**

<b>Country(s) or region</b>	<b>Inventory name</b>	<b>On inventory (yes/no)*</b>
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

**16. Other information, including date of preparation or last revision**

<b>Issue date</b>	04-25-2019
<b>Version #</b>	01
<b>Disclaimer</b>	Our company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.
<b>Revision information</b>	This document has undergone significant changes and should be reviewed in its entirety.